



## Ultra Drain Guards

**Ultra Drain Guards are designed to remove oil and sediment pollution from surface water running into gully drains from surrounding construction sites, farms, industrial estates, or other areas prone to storm water pollution or cleaning operations.**

Ultra Drain Guards are made from a high permeability non-woven polypropylene geotextile that trap solids and oils but allow water to drain through and also incorporate bypass ports to further maintain flow into the drain.

They are designed to be easily placed directly into the drain gully pot to filter out materials as they flow into the drain without compromising drainage, and the Oil and Sediment model absorbs up to 3.29 litres of hydrocarbons as well as up to 18 kg of sediment, sand or debris.

### Installation

1. Remove catch basin grating
2. Clean dirt and debris from grating ledge
3. Insert Drain Guard.
4. Reinstall grate. To insure maximum effectiveness, Drain Guard skirt should be secured (pinched) between grating and ledge.
5. Cut the excess fabric off with a blade or knife if desired.

### Maintenance and disposal

6. The Ultra-Drain Guard filters are designed to be used for 3 to 6 months under normal conditions.
7. Where heavy contamination is present the unit will have a reduced life expectancy. When the unit has collected about 6 inches of sediment it is recommended that it be replaced. The unit should also be replaced if free oil can be seen floating and is not being absorbed. The Ultra-Drain Guards should be inspected on a regular basis.

### Guidance

- 25.4cm (diameter) x 45.7cm (depth) catchment area
- Cut the skirt to fit your drain

Application Categories: Sediment Pollution Control



Agrotextiles



Biodegradables



Geotextiles



Specialist



Wildlife



Living Walls &  
Roofs



Accessories



### Features/Benefits:

- Captures oil and sediment before it enters the drain
- Absorbs up to 3.29 litres of hydrocarbons
- Holds up to 18kg of sediment
- Easy installation and maintenance
- Universal fit
- Compact packaging means storage on site is not taken up
- Designed to be used for 3-6 months under normal conditions

Model	Code	Oil Capture	Sediment Capture	Collection Area	Flow Rate	Size
Oil & Sediment	9217	3.29 l (.87 gal)	18 kg (40 lbs)	25.4 x 45.7cm (10" x 18")	1893 L/min (500 gpm)	121.9 x 91.4 x 45.7cm (48" x 36" x 18")

Feature	ASTM Test	Value
Material		Non-woven polypropylene geotextile
Grab Tensile Strength	D 4632	979 N (220 lb)
Elongation	D 4632	50%
Trapezoid Tear	D 4533	423 N (95 lb)
Puncture Resistance	D 4833	600 N (135 lbs)
Mullen Burst	D 3786	2,896 kpa (420 psi)
Permittivity	D 4491	1.4 sec <sup>-1</sup>
Pore Size	D 4751	180 micron (80 US sieve no)
UV Stability	D 4355	70% strength retained after 500hr
Weight	D 5261	272 g/m <sup>2</sup> (8 oz/yd <sup>2</sup> )
Flow Rate - Fabric	D 4491	3,660 L/min/m <sup>2</sup> (90 gal/min/ft <sup>2</sup> )
Flow Rate - Bypass Ports	D 4491	2,914 L/min

All data stated and the recommendations made herein are offered free of charge and are accurate to the best of our knowledge. Hy-Tex (UK) Ltd assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. Hy-Tex disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, material, or information furnished herewith. Final determination of the use of any information or material, or how it is useful, and whether the use infringes any patents is the sole responsibility of the user.

Application Categories: Sediment Pollution Control

Hy-Tex (UK) Limited  
Aldington Mill, Mill Lane,  
Aldington, Ashford, Kent  
TN25 7AJ

01233 720097  
sales@hy-tex.co.uk  
www.hy-tex.co.uk  
01233 720098

